## **DENTSPLY International** DENTSPLY PROSTHETICS

## **Safety Data Sheet**

Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Date Issued: 09 August 2004 Document Number: 202 Date Revised: 3 February 2015 Revision Number:5

### 1. PRODUCT IDENTIFICATION

Trade Name (as labeled):

PermaSoft<sup>®</sup> Denture Liner Powder

Product Identifier (Part/Item Number): N811500, N811000, N812000, N812500, N811100, N812100, N815002, N815003, N815005, N815101, N815102, N815103, N815105.

U.N. Number:	None
U.N. Dangerous Goods Classification:	None
Recommended Use:	Denture liner.
Restrictions on Use:	For Professional Use Only
Manufacturer/Supplier Name:	<b>DENTSPLY</b> Prosthetics
Manufacturer/Supplier Address:	570 West College Ave.
	York, PA 17401
Manufacturer/Supplier Telephone Number:	717-845-7511 (Product Information)
Emergency Contact Telephone Number:	800-424-9300 Chemtrec
Email address:	<pre>Prosthetics_MSDS@Dentsply.com</pre>

### 2. HAZARD(s) IDENTIFICATION

EU Classification (1999/45/EC): Not Classified as Hazardous

Labeling in accordance with 1999/45/EC: None required

US Hazard Classification: Not Hazardous

### 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Components	C.A.S. #	EINECS #	Substance Classification	WT %
Non-hazardous Acrylic Polymer	Proprietary	Proprietary	Not applicable	90 - 100

### 4. FIRST-AID MEASURES

Routes of Exposure	First Aid Instructions
Eye	Flush eyes with water, holding the eyelids apart. Get medical attention if irritation persists.
Skin	Wash skin with soap and water. Get medical attention if irritation develops. Launder clothing before re-use.
Inhalation	Remove victim to fresh air. Get medical attention if irritation develops.
Ingestion	If small quantities are swallowed, rinse out mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. If irritation or discomfort occurs, get immediate medical attention.
Most important symptoms of exposure	Dust may cause mild eye and respiratory irritation. Individuals with sensitivity to methacrylates may develop an allergic reaction when exposed to this product.
Note to Physicians	(Treatment, Testing, and Monitoring)
Treat symptomatical	ly.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Medi	a: Use water spray, carbon	Use water spray, carbon dioxide, foam or dry chemical.		
Fire Fighting Procedures:	Cool exposed intact cont	Cool exposed intact containers with water spray.		
Specific Hazards Arising fro the Chemical:	<b>m</b> High concentrations of d	High concentrations of dust in air may be explosive.		
Precautions for Fire Fighters		Firefighters should wear full emergency equipment and approved positive pressure self-containing breathing apparatus.		
	<b>Recommended Protective Equipment for Fire Fighters</b> :			
EYES/FACE	HANDS	RESPIRATORY	THERMAL	

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions, PPE and Emergency Procedures**: Wear appropriate protective clothing as described in Section 8. Remove all sources of ignition. Avoid contact with skin, eyes or clothing.

**Environmental Precautions**: Do not allow spills or contaminated water to enter sewers, waterways, lakes, streams, ponds, groundwater, or soil. Report releases as required by local, state, and national authorities.

Methods and Materials for Containment and Clean-up: Carefully collect and place into a container for disposal. Do not generate airborne dust.

Recommended Personal Protective Equipment for Containment and Clean-up:			
EYES/FACE	HANDS	RESPIRATORY	THERMAL
	C C C C C C C C C C C C C C C C C C C		

### 7. HANDLING AND STORAGE

**Precautions for Safe Handing:** Avoid contact with eyes and skin. Avoid breathing dust or fumes. Wash thoroughly after handling. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Use good housekeeping to minimize accumulation of dust on equipment and surfaces. Keep away from sources of heat or ignition sources.

Empty containers retain product residues can be hazardous. Follow all MSDS precautions when handling empty containers.

**Conditions for Safe Storage:** Store in a cool, dry, well ventilated area. Keep container tightly closed when not in use. Store away from oxidizers.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:		
Non-hazardous Acrylic Polymer (as Particulates Not Otherwise	United States	15 mg/m <sup>3</sup> TWA OSHA PEL (Total Dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (Respirable)
Specified)	Germany	4 mg/m <sup>3</sup> TWA DFG MAK (Inhalable) 1.5 mg/m <sup>3</sup> TWA DFG MAK (Respirable)
	United Kingdom	10 mg/m <sup>3</sup> TWA UK OEL (Inhalable) 4 mg/m <sup>3</sup> TWA UK OEL (Respirable)
	European Union	None Established

Biological Exposure Limits: None established.

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to minimize exposures levels. Use explosion-proof equipment where needed.

### Individual Protection Measures (PPE)

Specific Eye/face Protection: Chemical safety glasses with side shields or chemical goggles.

**Specific Skin Protection:** Wear impervious gloves if needed to avoid skin contact. Recommended glove: Rubber. Consult glove supplier for thickness and breakthrough times.

**Specific Respiratory Protection:** None needed for normal use. If the exposure limits are exceeded an approved dust/mist respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with all applicable regulations and good industrial hygiene practice.

Recommended Personal Protective Equipment				
EYES/FACE	HANDS	RESPIRATORY	THERMAL	
	C C C C C C C C C C C C C C C C C C C			
Cnvironmental Exposure Cont	rols: None required for norm	al use.		
General Hygiene Consideratio fter handling. Wear clothing wi		void contact with eyes, skin, an	d clothing. Wash thorough	

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Pink or clear powder.	Explosive limits:	LEL: Not applicable UEL: Not applicable
Odor:	Slight odor.	Vapor pressure:	Not applicable
Odor threshold:	Not determined	Vapor density:	Not applicable
рН:	Not applicable	Relative density:	1.16
Melting/freezing point:	Not applicable	Solubility:	Insoluble
Initial boiling point and range:	Not applicable	Partition coefficient: n- octanol/water:	Not applicable
Flash point:	>482°F (>250°C)	Auto-ignition temperature:	>752°F (>400°C)
Evaporation rate:	Not applicable	Decomposition temperature:	482°F (250°C)
Flammability:	Non flammable	Viscosity:	Not applicable
Explosive Properties:	High concentrations of dust in air may be explosive.	Oxidizing Properties:	None

### **10. STABILITY AND REACTIVITY**

Reactivity: None known.

Chemical Stability: Stable.

Possibility of Hazardous Reactions: None known

**Conditions to Avoid**: Product will begin to depolymerization at 482°F (250°C). Keep product away from heat and ignition sources.

Incompatible materials: Avoid oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition may release carbon monoxide, carbon dioxide and ethyl methacrylate.

### **11. TOXICOLOGICAL INFORMATION**

#### **Potential Health Effects:**

Eyes: Dust may cause mechanical irritation.

Skin: May cause mechanical irritation. May cause skin sensitization is some individuals.

Ingestion: No adverse effects expected under normal use conditions.

<u>Inhalation:</u> Inhalation of dust may cause irritation of the eyes, nose and upper respiratory tract. Symptoms include coughing, sneezing and difficulty in breathing.

<u>Chronic Health Effects</u>: Prolonged or repeated overexposure may cause skin irritation or sensitization in some individuals.

<u>Carcinogenicity</u>: None of the components of this product listed at >0.1% are carcinogens by OSHA, IARC or NTP or the EU Substances Directive.

**Mutagenicity:** No data available. This product is not expected to cause mutagenic activity.

<u>Medical Conditions Aggravated by Exposure</u>: Individuals with pre-existing skin and respiratory disorders may be at increased risk from exposure.

### Acute Toxicity Data:

Non-hazardous Acrylic Polymer: No data available

**Reproductive Toxicity Data:** No data available. This product is not expected to cause adverse reproductive effects.

### Specific Target Organ Toxicity (STOT):

Single Exposure: No data available

Repeated Exposure: No data available

### **12. ECOLOGICAL INFORMATION**

**Toxicity**: No data available

Persistence and Degradability: No data available

Bio-accumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

Results of PBT/vPvB Assessment: No data available

### **13. DISPOSAL CONSIDERATIONS**

Regulations: Dispose in accordance with all national and local regulations.

Properties (Physical/Chemical) Affecting Disposal: None currently known.

Waste Treatment Recommendations: None known.

### **14. TRANSPORT INFORMATION**

ADR/RID: Not Regul			
IMDG: Not Regulated IATA: Not Regulated	d I		
ADR/RID: None	IMDG: None	IATA: None	DOT: None
ADR/RID: None	IMDG: None	IATA: None	DOT: None
ADR/RID: No	IMDG Marine pollutant: No	IATA: No	DOT: No
-	IATA: Not Regulated DOT: Not Regulated ADR/RID: None ADR/RID: None	IATA: Not Regulated DOT: Not Regulated ADR/RID: None IMDG: None ADR/RID: None IMDG: None ADR/RID: No IMDG Marine pollutant: No	IATA: Not RegulatedDOT: Not RegulatedADR/RID: NoneIMDG: NoneADR/RID: NoneIMDG: NoneADR/RID: NoneIMDG Marine pollutant: No

### **15. REGULATORY INFORMATION**

### **U.S. Federal Regulations**

US OSHA Hazard Classification: Non-hazardous.

**Comprehensive Environmental Response and Liability Act of 1980 (CERCLA):** This product is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**Toxic Substances Control Act (TSCA):** This product is a medical device and not subject to chemical notification requirements.

Clean Water Act (CWA): This material is not regulated under the Clean Water Act

Clean Air Act (CAA): This material is not regulated under the Clean Air Act

### Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Immediate Hazard:	No	Pressure Hazard:	No
Delayed Hazard:	No	Reactivity Hazard:	No
Fire Hazard:	No		

# This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): None

Components	C.A.S. #	WT %
None		

#### State Regulations

**California:** This product contains the following substances known to the state of California to cause cancer and/or reproductive toxicity:

Components	C.A.S. #	WT %
Titanium dioxide	13463-67-7	0.05

#### **International Regulations**

**Canadian Environmental Protection Act:** All of the components in this product are listed on the Domestic Substances List (DSL).

Canadian Workplace Hazardous Materials Information System (WHMIS): Not a controlled product.

**European Inventory of Existing Chemicals (EINECS):** This product is a medical device and not subject to chemical notification requirements.

EU REACH: All components requiring registration have been pre-registered.

Australian Inventory of Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

**China Inventory of Existing Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

Japanese Existing and New Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

**Korean Existing Chemicals List:** This product is a medical device and not subject to chemical notification requirements.

**Philippine Inventory of Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

### **16. OTHER INFORMATION**

 $\begin{array}{ll} \mbox{HMIS Hazard Rating:} \\ \mbox{Health} - 0 & \mbox{Flammability} - 1 & \mbox{Reactivity} - 0 \end{array}$ 

Full text of Classification abbreviations used in Section 2 and 3: None.

Supersedes: 24 January 2012 Date Revised: 3 February 2015 Revision Summary: Comprehensive review.

Data Sources: US NLM ChemID Plus and HSDB, Substance SDS for components, IUCLID Dataset EU Chemical Bureau, ESIS, Country websites for occupational exposure limits.

## **DENTSPLY International** DENTSPLY PROSTHETICS

## Safety Data Sheet

Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Date Issued: 5 September 2002 Document Number: 204 Date Revised: 13 August 2014 Revision Number: 6

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product Identifier:** Trade Name (as labeled): PermaSoft<sup>®</sup> Denture Liner Sealer N811000, N811100, N811500, N812000, N812100, **Part/Item Number:** N812500, N816002, N816005 **1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against: Recommended Use: Denture Liner Sealant Restrictions on Use:** For Professional Use Only **1.3 Details of the Supplier of the Safety Data Sheet:** Manufacturer/Supplier Name: **DENTSPLY** Prosthetics Manufacturer/Supplier Address: 570 West College Ave. York, PA 17401 Manufacturer/Supplier Telephone Number: 717-845-7511 (Product Information) **Email address: Prosthetics MSDS@Dentsply.com 1.4 Emergency Telephone Number: Emergency Contact Telephone Number:** 800-424-9300 Chemtrec

### 2. HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture:

GHS Classification:				
Health	Environmental	Physical		
Eye Irritant Category 2 (H319) Specific Target Organ Toxicity-	Not Hazardous	Flammable Liquid Category 2 (H225)		
Single Exposure Category 3 (H336)				

EU Classification: Highly Flammable (F), Irritant (Xi) R11, R36, R66, R67

### 2.2 Label Elements:



### Signal Word: Danger

Contains: Methyl Ethyl Ketone

Hazard Phrases	Precautionary Phrases
H225 Highly flammable liquid and vapour.	P210 Keep away from heat, sparks, open flames, and hot
H319 Causes serious eye irritation.	surfaces. No smoking.
H336 May cause drowsiness or dizziness.	P233 Keep container tightly closed.
	P240 Ground and bond container and receiving equipment
	P241 Use explosion-proof electrical, ventilating and
	lighting equipment.
	P242 Use only non-sparking tools.
	P243 Take precautionary measures against static discharge.
	P261 Avoid breathing mist, vapors, or spray.
	P264 Wash thoroughly after handling.
	P271 Use only outdoors or in a well-ventilated area.
	P280 Wear protective gloves, eye protection and face
	protection.
	P303 + P361 + P353 IF ON SKIN (or hair): Take off
	immediately all contaminated clothing. Rinse skin with
	water or shower.
	P305 + P351 + P338 IF IN EYES: Rinse cautiously with
	water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
	P337 + P313 If eye irritation persists: Get medical
	attention.
	P304 + P340 IF INHALED: Remove victim to fresh air
	and keep at rest in a position comfortable for breathing.
	P312 Call a POISON CENTER or doctor if you feel
	unwell.
	P370 + P378 In case of fire: Use carbon dioxide, alcohol
	foam or dry chemical to extinguish.
	P403 + P235 Store in a well-ventilated place. Keep cool.
	P405 Store locked up.
	P501 Dispose of contents and container in accordance with
	local and national regulations.

### 2.3 Other Hazards: None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 Mixture:

Hazardous Components	C.A.S. #	EINECS #	Classification	WT %
Methyl Ethyl Ketone (2-butanone)	78-93-3	201-159-0	) F, Xi R11, R36, R66, R67 70-95	
			Flam. Liq. 2, H225	
			Eye Irrit. 2, H319	
			STOT SE 3, H336	
Polymer	Proprietary	Proprietary	Not Applicable	5-30

The exact concentration is being withheld as a trade secret.

Refer to Section 16 for the full text of the GHS and EU Classifications.

### 4. FIRST AID MEASURES

#### 4.1 Description of First Aid Measures:

-	
Eye	Immediately flush eyes with large quantities of water for at least 15 minutes, while holding the eyelids apart. Get medical attention if irritation persists.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation or symptoms develop, get medical attention. Launder clothing before re-use.
Inhalation	Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get medical attention if breathing is difficult or irritation persists.
Ingestion	If small quantities are swallowed, rinse out mouth with water. Do not induce vomiting unless directed to do so by a medical professional. Get medical attention if symptoms develop or if you feel unwell.

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed:

Causes eye irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Prolonged and/or repeated overexposure may cause nervous system damage.

### 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed:

Immediate medical attention is not required.

Note to Physicians (Treatment, Testing, and Monitoring): Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

<b>5.1 Extinguishing Media:</b> Use water spray, carbon dioxide, alcohol foam or dry chemical.
------------------------------------------------------------------------------------------------

### 5.2 Special Hazards Arising from the Substance or Mixture:

This product is highly flammable and forms explosive mixtures with air. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to extreme heat. Decomposition may release carbon monoxide, carbon dioxide and unidentified organics.

5.3 Advice for Fire-Fighters:		
Fire Fighting Procedures:	Use water to cool exposed containers and structures and disperse flammable vapors.	
Precautions for Fire Fighters:	Firefighters should wear full emergency equipment and an approved positive pressure self- contained breathing apparatus.	
righters.	contained oreating appartures.	

<b>Recommended Protective Equipment for Fire Fighters:</b>			
EYES/FACE HANDS RESPIRATORY THERMAL			
	C C C C C C C C C C C C C C C C C C C		

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Evacuate spill area and keep unprotected personnel away. Remove all sources of ignition. Avoid breathing vapors or mists. Ventilate area with explosion proof equipment. Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Wear appropriate protective clothing as described in Section 8. If spill has not ignited, use water spray to disperse the vapors and protect personnel attempting to stop leak.

#### Recommended Personal Protective Equipment for Containment and Clean-up:

EYES/FACE	HANDS	RESPIRATORY	SKIN
	Contraction of the second seco		

### 6.2 Environmental Precautions:

Do not allow spills to enter sewers, waterways or the environment. Report releases as required by local, state and federal authorities.

### 6.3 Methods and Material for Containment and Cleaning up:

Eliminate all ignition sources. Contain and collect using inert absorbent materials and place in appropriate containers for disposal. Use non-sparking tools and equipment.

### 6.4 Reference to Other Sections:

Refer to Section 8 for Personal Protective Equipment and Section 13 for Disposal information.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for Safe Handing:

Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Avoid breathing vapors or mists. Wear protective clothing and equipment as described in Section 8. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep product away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas. Use with non-sparking tools and explosion proof equipment. Electrically bond and ground containers for transfer.

Do not cut, drill, grind or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

**7.2 Conditions for Safe Storage, Including Any Incompatibilities:** Store in accordance with regulations for the storage of flammable liquids. Store in a dry, well-ventilated area away from heat, direct sunlight and all sources of ignition. Store away from oxidizers and other incompatible materials.

**7.3 Specific End Use (s):** For professional use only.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters:				
Occupational Exposure Limi	ts:			
Methyl Ethyl Ketone	United States	200 ppm TWA, 300 ppm STEL ACGIH TLV 200 ppm TWA OSHA PEL		
	Germany	200 ppm TWA, 200 ppm STEL DFG MAK (skin)		
	United Kingdom	200 ppm TWA, 300 ppm STEL UK WEL		
	European Union	200 ppm TWA, 300 ppm STEL EU OEL		
Polymer	United States	None Established		
	Germany	None Established		
	United Kingdom	None Established		
	European Union	None Established		

#### **Biological Exposure Limits:**

Methyl Ethyl Ketone: Methyl ethyl ketone in urine, End of shift, 2 mg/L.

### 8.2 Exposure Controls:

**Appropriate Engineering Controls:** Use ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Use explosion-proof equipment where required

### Individual Protection Measures (PPE):

Specific Eye/face Protection: Chemical splash goggles recommended.

**Specific Skin Protection:** Wear impervious gloves such as butyl rubber to avoid prolonged skin contact. Clothing with long sleeves may be needed when working with large quantities.

**Specific Respiratory Protection:** None should be needed for normal use. If the exposure limits are exceeded an approved organic vapor respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with applicable regulations and good industrial hygiene practice.

Specific Thermal Hazards: None required

Recommended Personal Protective Equipment				
EYES/FACE	HANDS	RESPIRATORY	SKIN	

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on Basic Physical and Chemical Properties:

Appearance:	Colorless liquid	Explosive limits:	LEL: 1.4% (Methyl Ethyl Ketone) UEL: 11.4% (Methyl Ethyl
-------------	------------------	-------------------	----------------------------------------------------------------

			Ketone)
Odor:	Characteristic sweetish odor	Vapor pressure (mmHg):	77.5 mmHg @ 68°F (20°C)
Odor threshold:	Not available	Vapor density:	2.5
рН:	Not available	Relative density:	0.80
Melting/freezing point:	-123°F (-86°C)	Solubility(ies):	29 g/100 mL
Initial boiling point and boiling range:	176°F (80°C)	Partition coefficient: n- octanol/water:	Not available
Flash point:	23°F (-5°C)	Auto-ignition temperature:	Not available
Evaporation rate:	Not available	Decomposition temperature:	Not available
Flammability (solid, gas):	Not applicable	Viscosity:	Not available
Explosive Properties:	Vapors may be explosive in confined areas.	Oxidizing Properties:	None

9.2 Other Information: None available.

### **10. STABILITY AND REACTIVITY**

**10.1 Reactivity:** None known.

10.2 Chemical Stability: Stable under normal conditions. Reacts with strong oxidizing agents.

**10.3 Possibility of Hazardous Reactions:** Methyl Ethyl Ketone may react violently with strong oxidants and inorganic acids causing fire and explosion hazard. Methyl Ethyl Ketone can attack some plastic.

10.4 Conditions to Avoid: Keep away from heat, sparks and all ignition sources.

**10.5 Incompatible materials:** Avoid oxidizing agents, inorganic acids, copper, hydrogen peroxide, chloroform and halogens.

**10.6 Hazardous Decomposition Products:** Decomposition may release carbon monoxide, carbon dioxide and unidentified organics.

### **11. TOXICOLOGICAL INFORMATION**

### **11.1 Information on Toxicological Effects:**

### Potential Health Effects:

Eyes: Contact may cause irritation with redness, tearing and stinging.

<u>Skin:</u> Prolonged contact may cause irritation with redness, itching and pain. The liquid may be absorbed through the skin causing effects similar to those described under inhalation and ingestion.

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation and nervous system depression with

symptoms of headache, dizziness, abdominal pain, nausea, vomiting and unconsciousness.

<u>Inhalation</u>: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, drowsiness, fatigue, nausea, shortness of breath, confusion, and unconsciousness.

<u>Chronic Health Effects</u>: Prolonged occupational overexposure may cause defatting of the skin, dermatitis and damage to the nervous system. Methyl ethyl ketone has been found to cause adverse reproductive effects and/or birth defects in studies with laboratory animals.

Irritation: Methyl ethyl ketone: Irritating to rabbit eyes. Not irritating to rabbit skin.

**<u>Corrosivity</u>**: No data available. This product is not expected to be corrosive.

Sensitization: No data available. This product is not expected to cause sensitization.

<u>Carcinogenicity</u>: None of the components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH or the EU CLP.

<u>Mutagenicity</u>: Methyl ethyl ketone: Mutagenicity studies on MEK. The test systems comprised the Salmonella/microsome (Ames) assay, the L5178/TK+/- mouse lymphoma (M/L) assay, the BALB/3T3 cell transformation (CT) assay, unscheduled DNA synthesis (UDS) and the micronucleus test. MEK was not found to be genotoxic in these assays.

Medical Conditions Aggravated by Exposure:

Individuals with pre-existing skin conditions may be at increased risk from exposure.

#### Acute Toxicity Data:

Methyl ethyl ketone: Oral rat LD50-2193 mg/kg; Dermal rabbit LD50->8000 mg/kg; Inhalation rat LC50->5000 ppm/6 hr.

**<u>Reproductive Toxicity Data:</u>** Methyl ethyl ketone has been found to cause adverse reproductive effects and/or birth defects in studies with laboratory animals.

### Specific Target Organ Toxicity (STOT):

<u>Single Exposure</u>: Methyl ethyl ketone: CNS depression/ and other nerve dysfunctions. The common symptoms of short term exposure are fatigue, headache, nausea, sleep disturbance, and alteration in memory. Psychomotor performance of adverse effects on intellectual or memory functions are demonstrated with psychological test batteries after long-term occupational exposure to organic solvents.

<u>Repeated Exposure</u>: Methyl ethyl ketone: Male and female Fischer 344 rats were exposed to 0, 1250, 2500, or 5000 ppm methyl ethyl ketone (MEK) vapors 6 hr/day, 5 day/wk for 90 days. The 90 day exposures had no adverse effect on the clinical health or growth of male or female rats except for a depression of mean body wt in the 5000 ppm exposure group. The 5000 ppm animals had a slight but significant increase in liver weight, liver weight/body weight ratio, and liver weight/brain weight ratio at necropsy.

### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity:

Methyl ethyl ketone: 96hr LC50 Fathead minnow- 2993 mg/L; 48hr EC50 Daphnia magna- 308 mg/L

**12.2 Persistence and Degradability:** Methyl ethyl ketone (MEK) is readily oxidized by microorganisms in activated sludge following selection and/or adaptation, with over 80% being removed in 24 hr.

**12.3 Bio-accumulative Potential:** Methyl ethyl ketone: An estimated BCF of 3 was calculated in fish for methyl ethyl ketone, using a log Kow of 0.29 and a regression-derived equation. According to a classification scheme, this BCF suggests the potential for bioconcentration in aquatic organisms is low.

**12.4 Mobility in Soil:** Methyl ethyl ketone is expected to have very high mobility in soil.

12.5 Results of PBT and vPvB Assessment: Not required

**12.6 Other Adverse Effects:** None known.

### **13. DISPOSAL CONSIDERATIONS**

**13.1 Waste Treatment Methods:** 

Regulations: Dispose in accordance with all national and local regulations.

**Properties (Physical/Chemical) Affecting Disposal:** Empty containers retain product residues and can be hazardous. Follow all SDS precautions when handling empty containers.

Waste Treatment Recommendations: Treat in accordance with national and local regulations.

	14.1 UN Number	14.2 UN Proper Shipping Name	14.3 Hazard Class(s)	14.4 Packing Group	14.5 Environmental Hazards
DOT	UN1193	Methyl Ethyl Ketone	3	II	No
ADR/RID	UN1193	Methyl Ethyl Ketone	3	II	No
IMDG	UN1193	Methyl Ethyl Ketone	3	II	No
IATA/ICAO	UN1193	Methyl Ethyl Ketone	3	II	No

### **14. TRANSPORT INFORMATION**

14.6 Special Precautions for User: Not applicable.

**14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable - product is transported only in packaged form.

### **15. REGULATORY INFORMATION**

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture:

### **U.S. Federal Regulations**

**Comprehensive Environmental Response and Liability Act of 1980 (CERCLA):** This product has a Reportable Quantity (RQ) of 5,263 lbs. (based on the RQ for Methyl Ethyl Ketone of 5,000 lbs present at 75-95%). Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act (TSCA): This product is a medical device and not subject to chemical notification.

Clean Water Act (CWA): This material is not regulated under the Clean Water Act.

Clean Air Act (CAA): This material is not regulated under the Clean Air Act

### Superfund Amendments and Reauthorization Act (SARA) Title III Information:

### SARA Section 311/312 (40 CFR 370) Hazard Categories:

Immediate Hazard:	Yes	Pressure Hazard:	No
Delayed Hazard:	No	Reactivity Hazard:	No

Fire Hazard:	Yes	
--------------	-----	--

# This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):

Components	C.A.S. #	WT %
None		

#### State Regulations

**California:** This product contains the following substances known to the state of California to cause cancer and/or reproductive toxicity:

Components	C.A.S. #	WT %
Acetaldehyde	75-07-0	<83.6 ppm
Vinyl Chloride	75-01-4	<83.6 ppm

#### **International Regulations**

Canadian Workplace Hazardous Materials Information System (WHMIS): Medical devices are not covered by WHMIS.

**Canadian Environmental Protection Act:** This product is a medical device and not subject to chemical notification requirements.

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

**European Inventory of Existing Chemicals (EINECS):** This product is a medical device and not subject to chemical notification requirements.

EU REACH: This product is a medical device and not subject to chemical notification requirements.

**Australian Inventory of Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

**China Inventory of Existing Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

**Korean Existing Chemicals List:** This product is a medical device and not subject to chemical notification requirements.

**Philippine Inventory of Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

15.2 Chemical Safety Assessment: None required.

### **16. OTHER INFORMATION**

HMIS Hazard Rating: Health – 2 Flammability – 3 Physical Hazard– 0 Full text of Classification abbreviations used in Section 2 and 3: F Flammable Xi Irritant R11 Highly flammable. R36 Irritating to eyes. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapors may cause drowsiness and dizziness

Flam. Liq. 2 Flammable Liquid Category 2
Eye Irrit. 2A Eye Irritant Category 2A
STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3
H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supersedes: 20 April 2012 Revision Summary: Converted SDS to Reach SDS. Updated all sections.

Data Sources: US NLM ChemID Plus and HSDB, Substance SDS for components, IUCLID Dataset EU Chemical Bureau, ESIS, Country websites for occupational exposure limits.

## **DENTSPLY International** DENTSPLY PROSTHETICS

## Safety Data Sheet

Safety Data Sheet (in compliance with Regulation (EC) 1907/2006, Regulation (EC) 1272/2008 and Regulation (EC) 453/2010)

Date Issued: 9 August 2004 Document Number: 203 Date Revised: 18 December 2013 Revision Number: 7

### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product Identifier:** 

Trade Name (as labeled): Part/Item Number: PermaSoft® Liquid

N811000, N811100, N811500, N812000, N812100, N812500, N814002, N814005

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against:

<b>Recommended Use:</b>	Denture Liner
<b>Restrictions on Use:</b>	For Professional Use Only
1.3 Details of the Supplier of the Safety Data Sheet:	
Manufacturer/Supplier Name:	<b>Dentsply Prosthetics</b>
Manufacturer/Supplier Address:	570 West College Ave.
	York, PA 17401
Manufacturer/Supplier Telephone Number:	717-845-7511 (Product Information)
Email address:	Prosthetics_MSDS@Dentsply.com
1.4 Emergency Telephone Number:	

**Emergency Contact Telephone Number:** 

800-424-9300 Chemtrec

### 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the Substance or Mixture:

GHS Classification:				
Health	Environmental	Physical		
Eye Irritant Category 2 Reproductive Toxicity Category 1B	Aquatic Acute Category 1	Flammable Liquid Category 3		

EU Classification: Toxic (T) Dangerous for the Environment (N), R10, R50, R61, R62

### 2.2 Label Elements:



### Signal Word: Danger

Contains: Dibutyl Phthalate

Hazard Phrases	Precautionary Phrases
H226 Flammable Liquid and vapor.	
H319 Causes serious eye irritation.	P201 Obtain special instructions before use.
H360df May damage the unborn child. Suspected of damaging fertility.	P202 Do not handle until all safety precautions have been read and understood
H400 Very toxic to aquatic life.	P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.
	P233 Keep container tightly closed.
	P240 Ground and bond container and receiving equipment P241 Use explosion-proof electrical, ventilating and
	lighting equipment.
	P242 Use only non-sparking tools.
	P243 Take precautionary measures against static discharge. P264 Wash thoroughly after handling.
	P280 Wear protective gloves, eye protection and face
	protection.
	P303 + P361 + P353 IF ON SKIN (or hair): Take off
	immediately all contaminated clothing. Rinse skin with water.
	P305 + P351 + P338 IF IN EYES: Rinse cautiously with
	water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337 + P313 If eye irritation persists: Get medical
	attention.
	P308 + P313 IF exposed or concerned: Get medical
	attention.
	P370 + P378 In case of fire: Use carbon dioxide, alcohol
	foam or dry chemical to extinguish.
	P273 Avoid release to the environment.
	P391 Collect spillage
	P403 + P235 Store in a well-ventilated place. Keep cool.
	P405 Store locked up.
	P501 Dispose of contents and container in accordance with
	local and national regulations.

### 2.3 Other Hazards: None known.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 Mixture:

Hazardous Components	C.A.S. #	EINECS #	Classification	WT %
Dibutyl Phthalate	84-74-2	201-557-4	T, N R50, R61, R62	60-90
			Repr. 1B H360,	
			Aquatic Acute 1 H400	

Ethyl Acetate	141-78-6	205-500-4	F, Xi R11, R36, R66, R67 Flam. Liq. 2 H225, Eye Irrit. 2A H319 STOT SE 3 H336	5-15
Ethanol (Ethyl Alcohol)	64-17-5	200-578-6	F R11 Flam. Liq. 2 H225	1-10

The exact concentration is being withheld as a trade secret.

Refer to Section 16 for the full text of the GHS and EU Classifications.

### 4. FIRST AID MEASURES

4.1 Descripti	4.1 Description of First Aid Measures:			
Eye	Immediately flush eyes with large quantities of water for at least 15 minutes, holding the eyelids apart. Get medical attention if irritation persists.			
Skin	Remove contaminated clothing. Immediately wash skin thoroughly with soap and water. If rash, irritation or symptoms develop, get medical attention. Launder clothing before re-use. (Discard contaminated shoes).			
Inhalation	Immediately remove victim to fresh air. If breathing is difficult have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get immediate medical attention.			
Ingestion	Get immediate medical attention. Immediately call poison control center or go to a hospital emergency room. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious or convulsing person.			

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed:

May cause eye and skin irritation. Inhalation of vapors or mist may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Prolonged and/or repeated overexposure may cause anemia, kidney and liver damage. May cause adverse reproductive effects based on studies with laboratory animals.

### 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed:

Immediate medical attention is required for ingestion and inhalation.

Note to Physicians (Treatment, Testing, and Monitoring): Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing Media:	Use carbon dioxide, alcohol foam or dry chemical.				
5.2 Special Hazards Arising	5.2 Special Hazards Arising from the Substance or Mixture:				
This product is flammable and forms explosive mixtures with air. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back. Closed containers may explode if exposed to extreme heat.					
5.3 Advice for Fire-Fighters:					
<b>Fire Fighting Procedures:</b> Use water to cool exposed containers and structures and disperse flammable vapors. Do not allow run-off from firefighting to enter drains or water courses.					
Precautions for Fire					
Fighters: contained breathing apparatus.					

	<b>Recommended Protective Equipment for Fire Fighters:</b>			
EYES/FACE	HANDS	RESPIRATORY	THERMAL	
Ey	Can and a second s			

### 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures:

Evacuate spill area and keep unprotected personnel away. Remove all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing as described in Section 8. Avoid contact with eyes, skin, and clothing. If spill has not ignited, use water spray to disperse the vapors and protect personnel attempting to stop leak.

Recommended Personal Protective Equipment for Containment and Clean-up:



#### 6.2 Environmental Precautions:

Do not flush into sewer! Do not allow spills to enter sewers, waterways or the environment. Report releases as required by local, state and federal authorities.

### 6.3 Methods and Material for Containment and Cleaning up:

Eliminate all ignition sources. Contain and collect using inert absorbent materials and place in appropriate containers for disposal. Use non-sparking tools and equipment.

### 6.4 Reference to Other Sections:

Refer to Section 8 for Personal Protective Equipment and Section 13 for Disposal information.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for Safe Handing:

Avoid contact with the eyes, skin and clothing. Avoid breathing vapors. Wear protective clothing and equipment as described in Section 8. Use only with adequate ventilation. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep product away from heat, sparks, flames and all other sources of ignition. Do not permit smoking in use or storage areas. Use with non-sparking tools and explosion proof equipment. Electrically bond and ground containers for transfer.

Do not cut, drill, grind or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

**7.2 Conditions for Safe Storage, Including Any Incompatibilities:** Store in accordance with regulations for the storage of flammable liquids. Store in a dry, well-ventilated area away from heat, direct sunlight and all sources of ignition. Store away from oxidizers and other incompatible materials.

**7.3 Specific End Use (s):** For professional use only.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters:				
Occupational Exposure Limits:				
Ethanol	United States	1000 ppm STEL ACGIH TLV 1000 ppm TWA OSHA PEL		
	Germany	500 ppm TWA, 1000 ppm STEL DFG MAK		
	United Kingdom	1000 ppm TWA UK WEL		
	European Union	Belgium: 1000 ppm TWA		
Dibutyl Phthalate	United States	5 mg/m <sup>3</sup> TWA ACGIH TLV 5 mg/m <sup>3</sup> TWA OSHA PEL		
	Germany	0.05 mg/m <sup>3</sup> TWA DFG MAK		
	United Kingdom	5 mg/m <sup>3</sup> TWA UK OEL 10 mg/m <sup>3</sup> STEL UK OEL		
	European Union	None Established		
Ethyl Acetate	United States	400 ppm TWA ACGIH TLV 400 ppm TWA OSHA PEL		
	Germany	400 ppm TWA DFG MAK		
	United Kingdom	200 ppm TWA UK OEL 400 ppm STEL UK OEL		
	European Union	None Established		

### **Biological Exposure Limits:**

None

### 8.2 Exposure Controls:

**Appropriate Engineering Controls:** Use ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Use explosion-proof equipment where required

### Individual Protection Measures (PPE):

Specific Eye/face Protection: Chemical safety glasses or chemical splash goggles recommended.

**Specific Skin Protection:** Wear impervious gloves such as  $4H^{TM}$ . Clothing with long sleeves may be needed when working with large quantities.

**Specific Respiratory Protection:** None should be needed for normal use. If the exposure limits are exceeded an approved organic vapor respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with applicable regulations and good industrial hygiene practice.

Specific Thermal Hazards: None required

Recommended Personal Protective Equipment			
EYES/FACE	HANDS	RESPIRATORY	SKIN
	CCUM/		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on Basic Physical and Chemical Properties:

Appearance:	Light colored liquid	Explosive limits:	LEL: 2.0% (as ethyl acetate) UEL: 19% (as ethyl alcohol)
Odor:	Slight odor	Vapor pressure (mmHg):	Not available
Odor threshold:	Not available	Vapor density:	9.6 @ 20°C
рН:	Not available	Relative density:	1.02
Melting/freezing point:	Not available	Solubility(ies):	Partially
Initial boiling point and boiling range:	171° F (77°C)	Partition coefficient: n- octanol/water:	Not available
Flash point:	74°F (23°C)	Auto-ignition temperature:	Not available
Evaporation rate:	Not available	Decomposition temperature:	Not available
Flammability (solid, gas):	Not applicable	Viscosity:	Not available
Explosive Properties:	Vapors may be explosive in confined areas.	Oxidizing Properties:	None

9.2 Other Information: None available.

### **10. STABILITY AND REACTIVITY**

10.1 Reactivity: None known.

**10.2 Chemical Stability:** Stable under normal conditions.

10.3 Possibility of Hazardous Reactions: None know.

10.4 Conditions to Avoid: Keep away from heat, sparks and all ignition sources.

10.5 Incompatible materials: Avoid oxidizing agents and inorganic acids.

### **10.6 Hazardous Decomposition Products:** Decomposition may release carbon monoxide and carbon dioxide.

### **11. TOXICOLOGICAL INFORMATION**

#### **11.1 Information on Toxicological Effects:**

#### Potential Health Effects:

Eyes: Contact may cause irritation with redness, tearing and stinging.

<u>Skin:</u> May cause skin irritation with redness and itching. Repeated or prolonged contact may cause drying, defatting of the skin and dermatitis.

<u>Ingestion:</u> Ingestion may cause mucous membrane and gastrointestinal irritation with nausea, vomiting and diarrhea. May cause nervous system depression with symptoms of headache, dizziness, nausea, vomiting, weakness, fatigue, confusion, and unconsciousness.

<u>Inhalation:</u> Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness, drowsiness, nausea, vomiting, and unconsciousness. High vapor concentrations may cause burning sensation of the nose and throat and watering of the eyes.

<u>Chronic Health Effects</u>: Repeated skin contact may cause dermatitis. Prolonged overexposure to ethyl acetate may cause anemia with leukocytes and damage to the kidney and liver.

**Irritation:** Ethanol: Not irritating to rabbit skin, Irritating to rabbit eyes.

**Corrosivity:** No data available. This product is not expected to be corrosive.

<u>Sensitization</u>: No data available. This product is not expected to cause sensitization. Dibutyl was not sensitizing in a guinea pig maximization test.

<u>Carcinogenicity</u>: Ethanol: Ingestion of alcoholic beverages is known to cause cancer in humans (IARC group 1). None of the components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH or the EU Directive.

<u>Mutagenicity</u>: Ethanol: Negative in AMES test, in-vivo rat cytogenetic assay. Positive in a sister chromatid and exchange CHO cells, human lymphocytes cytogenetic assay, in-vivo mouse cytogenetic assay and rat dominant lethal assay. Dibutyl was negative in an in vitro bacterial gene mutation assay.

#### Medical Conditions Aggravated by Exposure:

Individuals with pre-existing skin, respiratory, liver and kidney disease may be at increased risk from exposure.

#### Acute Toxicity Data:

Ethanol: Oral rat LD50-7060 mg/kg; Inhalation Rat LC50 – 117-125 mg/L/4 hr

Dibutyl Phthalate: LD50 oral rat 6279 mg/kg; LD50 skin rabbit 4200 mg/kg; LC50 inhalation mouse 15.68 mg/L/4 hr Ethyl Acetate: LD50 oral rat 5620 mg/kg; LC50 Inhalation Rat 200 gm/m3; LD50 Skin Rabbit > 20000 mg/kg

**Reproductive Toxicity Data:** Ethanol: Repeated ingestion of ethanol by pregnant mothers has been shown to adversely affect the central nervous system of the fetus, resulting in fetal alcohol syndrome. These effects include mental and physical retardation, disturbances of learning, motor and language deficiencies, behavioral disorders and small head size. Dibutyl phthalate has been shown to cause adverse reproductive effects and birth defects in studies with laboratory animals.

### Specific Target Organ Toxicity (STOT):

<u>Single Exposure</u>: May cause nervous system depression with symptoms of headache, dizziness, nausea, vomiting, weakness, fatigue, confusion, and unconsciousness.

<u>Repeated Exposure</u>: Ethanol: Ethanol when consumed as a beverage has been found to cause damage to the liver, nervous system and reproductive system. Prolonged overexposure to ethyl acetate may cause damage to the kidney and liver.

### **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity:

Dibutyl Phtalate: LC50 Pimephales promelas (Fathead minnow) 0.92 mg/L/96 hr; EC50 daphnia magna 4.8 mg/L/48 hr; EC50 Pseudokirchnerella subcapitata 0.75 mg/L/ 96 hr

Ethanol: LC50 rainbow trout 13000 mg/L/96 hr; LC50 daphnia magna 9268-14221 mg/L/48 hr; EC50 Chlorella pyrenoidosa (Green algae; growth inhibition) 9310 mg/L/48 hr

Ethyl Acetate: LC50 Pimephales promelas (fathead minnow) 230 mg/l/96 hr.

12.2 Persistence and Degradability: Ethanol and dibutyl phthalate are readily biodegradable in screening tests.

12.3 Bio-accumulative Potential: Ethanol has an estimated BCF of 3. Ethyl acetate has an estimated BCF of 3.2.

**12.4 Mobility in Soil:** Dibutyl phthalate is expected to have a low mobility in soil. Ethyl acetate is expected to have high mobility in soil.

12.5 Results of PBT and vPvB Assessment: Not required

**12.6 Other Adverse Effects:** None known.

### **13. DISPOSAL CONSIDERATIONS**

**13.1 Waste Treatment Methods:** 

Regulations: Dispose in accordance with all national and local regulations.

**Properties (Physical/Chemical) Affecting Disposal:** Empty containers retain product residues and can be hazardous. Follow all SDS precautions when handling empty containers.

Waste Treatment Recommendations: Treat in accordance with national and local regulations.

### **14. TRANSPORT INFORMATION**

	14.1 UN Number	14.2 UN Proper Shipping Name	14.3 Hazard Class(s)	14.4 Packing Group	14.5 Environmental Hazards
DOT	UN1993	Flammable Liquid n.o.s. (Ethanol, Ethyl Acetate)	3	III	No
ADR/RID	UN1993	Flammable Liquid n.o.s. (Ethanol, Ethyl Acetate)	3	III	No
IMDG	UN1993	Flammable Liquid n.o.s. (Ethanol, Ethyl Acetate)	3	III	No
IATA/ICAO	UN1993	Flammable Liquid n.o.s. (Ethanol, Ethyl Acetate)	3	III	No

14.6 Special Precautions for User: Not applicable.

**14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code:** Not applicable - product is transported only in packaged form.

### **15. REGULATORY INFORMATION**

#### 15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture:

#### **U.S. Federal Regulations**

**Comprehensive Environmental Response and Liability Act of 1980 (CERCLA):** This product has a Reportable Quantity (RQ) of 11 lbs. based on the RQ for Dibutyl Phthalete of 10 lbs. Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

Toxic Substances Control Act (TSCA): This product is a medical device and not subject to chemical notification.

Clean Water Act (CWA): This material is not regulated under the Clean Water Act.

Clean Air Act (CAA): This material is not regulated under the Clean Air Act

#### Superfund Amendments and Reauthorization Act (SARA) Title III Information:

#### SARA Section 311/312 (40 CFR 370) Hazard Categories:

Immediate Hazard:	Yes	Pressure Hazard:	No
Delayed Hazard:	Yes	Reactivity Hazard:	No
Fire Hazard:	Yes		

# This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372):

Components	C.A.S. #	WT %
Dibutyl Phthalate	84-74-2	60-90

#### State Regulations

**California:** This product contains the following substances known to the state of California to cause cancer and/or reproductive toxicity:

Components	C.A.S. #	WT %
Dibutyl Phthalate	84-74-2	60-90

#### **International Regulations**

Canadian Workplace Hazardous Materials Information System (WHMIS): Medical devices are not covered by WHMIS.

**Canadian Environmental Protection Act:** This product is a medical device and not subject to chemical notification requirements.

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

**European Inventory of Existing Chemicals (EINECS):** This product is a medical device and not subject to chemical notification requirements.

EU REACH: All components requiring registration have been pre-registered.

Australian Inventory of Chemical Substances: This product is a medical device and not subject to chemical notification requirements.

**China Inventory of Existing Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

**Korean Existing Chemicals List:** This product is a medical device and not subject to chemical notification requirements.

**Philippine Inventory of Chemicals and Chemical Substances:** This product is a medical device and not subject to chemical notification requirements.

15.2 Chemical Safety Assessment: None required.

### **16. OTHER INFORMATION**

HMIS Hazard Rating: Health  $-2^*$ Flammability – 3 Physical Hazard-0 Full text of Classification abbreviations used in Section 2 and 3: F Flammable N Dangerous for the Environment T Toxic Xi Irritant R10 Flammable R11 Highly flammable. R36 Irritating to eyes. R50 Very toxic to aquatic organisms. R61 May cause harm to the unborn child. R62 Possible risk of impaired fertility. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapors may cause drowsiness and dizziness Flam. Liq. 2 Flammable Liquid Category 2 Eye Irrit. 2A Eye Irritant Category 2A STOT SE 3 Specific Target Organ Toxicity Single Exposure Category 3 Repro 1B Toxic tot Reproduction Category 1B Aquatic Acute 1 Aquatic Acute Toxicity Category 1 H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H360df May damage the unborn child. Suspected of damaging fertility. H400 Very toxic to aquatic life. Supersedes: 1 February 2012 Revision Summary: Converted SDS to Reach SDS. Updated all sections. Data Sources: US NLM ChemID Plus and HSDB, Substance SDS for components, IUCLID Dataset EU Chemical Bureau, ESIS, Country websites for occupational exposure limits.